



SOUL LED



☆ SOUL LED

m² 0,048
500x445x215mm

1 Pcs
30 pcs



CODICE Code	CABLAGGIO Wiring	POTENZA Power(W)	FLUSSO NOM. Typical Flux(lm)	COLORE LED Beam colour(K)	CORRENTE Current(A)	PESO NETTO Net weight(Kg)	SORGENTE Light source	COLORE Colour	ENEC
505603.000	NC x LED					9,45	Philips LUXEON M	■	
505643.104	4 LED	32W	4160	4000	0,7	9,85	Philips LUXEON M	■	✓
505643.208	8 LED	64W	8320	4000	0,7	10,25	Philips LUXEON M	■	✓
505643.312	12 LED	96W	12480	4000	0,7	10,65	Philips LUXEON M	■	✓
505643.416	16 LED	128W	16640	4000	0,7	10,68	Philips LUXEON M	■	✓
505643.520	20 LED	160W	20800	4000	0,7	10,71	Philips LUXEON M	■	✓
505643.624	24 LED	192W	24960	4000	0,7	10,74	Philips LUXEON M	■	✓



Corpo, copertura integrale e blocco di fissaggio: pressofusione di alluminio.

Blocco di fissaggio: adatto per pali ø 60 mm, mentre per fissaggio a palo ø 40 mm è necessario un adattatore.

Verniciatura: polvere di poliestere termoindurente.

Piastra porta componenti: nylon rinforzato fibra di vetro facilmente removibile.

Vetro di protezione: temperato 4 mm.

Moduli LED: forniti con lente stradale e vertice di asimmetria a 30°.

Alimentazione: elettronica 220-240V 50-60Hz, protezione alla scarica sino a 6Kv, protezione termica NTC.

Disponibile a richiesta:

· Alimentatore DALI e Bipotenza



Housing, integral cover and pole fixing block: die-cast aluminium.

Fixing block: suitable for ø 60 mm poles, adapter is required for ø 40 mm poles.

Paintwork: thermosetting polyester powder.

Wiring plate: easily removable nylon fiber glass.

Protection glass: tempered 4 mm.

LED modules: supplied with road lens with asymmetry vertex at 30°.


Power supply: 220-240V 50-60Hz with electronic ballast, surge protection 6Kv, NTC thermal sensor.

Available on request:

· DALI and Bi-Power ballast

COLORI DISPONIBILI
Available colours

3 Antracite RAL 7039
RAL 7039 Anthracite



12 LED 96W 12480lm



Il prodotto può essere montato in posizione orizzontale.

The product can be mounted in a horizontal position.

